



Product: **ECOFREEZE**

Description: Anti-freeze protective fluid formulated with propylene glycol and special additives, which allow its use both in the motor transport and in the industrial circuits of the food/pharmaceutical sector. The special additives allow the gasket regeneration and the removal of the lime deposits thus making this fluid fit for the motor vehicles with high mileage (100.00 Km) to restore the efficiency of the cooling system.

Specification: SAE J 1034
CUNA NC 956.16
ASTM D 3306 and 498

Properties:

Specifications	Test Method	Unit	Value
Appearance	VISUAL		Clear
Color	VISUAL	c.c.r.	Colorless
Specific Weight 20/20°C	ASTM D 1122	Kg/l	1.037
Chloride (NaCl)	ASTM D 1384	ppm	<5
Sulfate (So4)	ASTM D 1384	ppm	<5
Acidity (CH3C00H)	ASTM D 1384	ppm	<10
Iron and Metals	ASTM D 1384	ppm	<5
Anhydrous Title	ASTM D 1384	% Peso	99.6
Water	ASTM D 1123	% Peso	0.050

MIXING TABLE					
ANTIFREEZE	20%	30%	40%	50%	52%
FREEZING POINT (°C)	-9	-17	-26	-36	-41
BOILING POINT (°C)	+118	+120	+122	+123	+125